Kawasaki NINJA ZX-25R 2020

FITTING INSTRUCTIONS TO BE FITTED BY A QUALIFIED TECHNICIAN



THIS SHEET INCLUDES FITTING INSTRUCTIONS FOR THE FOLLOWING PARTS:

Secondary Alternator Cover Part No. EC-ZX-25R-2020-1-GBR / Secondary Clutch Cover Part No. EC-ZX-25R-2020-2-GBR / Secondary Pulse Cover Part No. EC-ZX-25R-2020-3-GBR / Bullet Frame Sliders Part No. FS-ZX-25R-2020-LHS-S & FS-ZX-25R-2020-RHS-S



SECONDARY ALTERNATOR COVER PART NO. EC-ZX-25R-2020-1-GBR

- Remove lower fairing panel.
- 2. Remove 4 existing bolts from the stock Alternator cover, shown as position Bolt 1, 2, 3 & 4.
- Place the Secondary Alternator Cover over the stock cover.
- Assemble 4 replacement bolts loosely in the correct position as shown.
- 5. Tighten bolts to a Torque of 11Nm as per manufacturer's recommendations. DO NOT OVERTIGHTEN.
- Re-fit lower fairing panel. 6






SECONDARY CLUTCH COVER PART NO. EC-ZX-25R-2020-2-GBR

- 1. Remove lower fairing panel.
- 2. Remove 4 existing bolts from the Clutch cover, shown as position Bolt 1, 2, 3 & 4.
- 3 Place the Secondary Clutch Cover over the stock cover.
- 4. Assemble 4 replacement bolts loosely in the correct position as shown.
- Tighten bolts to a Torque of 11Nm as 5. per manufacturer's recommendations. DO NOT OVERTIGHTEN.
- Re-fit lower fairing panel. 6







SECONDARY PULSE COVER PART NO. EC-ZX-25R-2020-3-GBR

- 1. Remove lower fairing panel.
- Remove 3 existing bolts from the Pulse cover, shown as position Bolt 1, 2 & 3.
- Place the Secondary Pulse Cover over 3. the stock cover.
- Assemble 3 replacement bolts loosely 4. in the correct position as shown.
- 5. Tighten bolts to a Torque of 11Nm as per manufacturer's recommendations.
- Re-fit lower fairing panel. 6.

DO NOT OVERTIGHTEN.







Kawasaki NINJA ZX-25R 2020

FITTING INSTRUCTIONS TO BE FITTED BY A QUALIFIED TECHNICIAN



BULLET FRAME SLIDER SET - PART NO. FS-ZX-25R-2020-S:

BULLET FRAME SLIDER - LEFT HAND SIDE - STREET PART NO. FS-ZX-25R-2020-LHS-S

- 1 Remove upper engine mounting bolt, located through the fairing opening.
- 2 Assemble bolt through the aluminium bush into correct position.
- 3 Tighten to 40NM torque.
- 4 Slide bullet moulding onto aluminium bush.
- 5 Screw M6 bolt into front of bullet moulding hand tight.





BULLET FRAME SLIDER - RIGHT HAND SIDE - STREET PART NO. FS-ZX-25R-2020-RHS-S

- 1 Remove upper engine mounting bolt, located through the fairing opening.
- 2 Assemble bolt through the aluminium bush into correct position.
- 3 Tighten to 40NM torque.
- 4 Slide bullet moulding onto aluminium bush.
- 5 Screw M6 bolt into front of bullet moulding hand tight.



